

## COMETEO Professional Multi-Plate Radiation Shield for Weather Sensors

Termékkód: F8004



Professzionális passzív napsugárzás és időjárás elleni védelem a meteorológiai érzékelők, távadók és adatgyűjtők számára a jobb és a pontosabb mérés érdekében, természetes szellőzés mellett.

**WINNER of the Intercomparison of Thermometer Screens in the Arctic under the auspices of the World Meteorological Organization - WMO**

Multi-plate radiation shield is used to protect weather monitor systems and provides the most accurate climate measurement results. The uniquely designed screen minimizes solar radiation reaching the sensor, minimizes radiation absorbed by the screen and maximizes ambient air flow around the weather station sensor. The surface exposed to sunlight is made of highly reflective UV and long-term stable ASA plastic. The inner surfaces of the screen are made of matt black plastic to minimize internal reflections. Large 210mm diameter of 14 plates is designed to provide full protection of weather sensor

Each of the fourteen black louvers is equipped with a circular slot allowing air to flow vertically through the entire radiation shield. The slot also separates the sunlit part of the louver from the inner part and thus prevents heat transfer to the sensors.

Thermometer screen is designed for the installation of up to four sensors with a diameter of 13 to 18 mm.

Excellent wasp and bug deterrence. Sophisticated design prevents insects from building nests inside and thus degrading measurement.

Low cost replacement for Stevenson screen, taking advantage of reduced maintenance and better performance due to the low time constant compared to the traditional Stevenson screen.

**Can be used with most instruments and probes, e.g. Vaisala, Rotronic.**

### Műszaki adatok

MŰSZAKI ADATOK	.
Működési hőmérséklet tartomány	-40...+65 °C
Működési relatív páratartalom tartomány	0...100 % RH
Tárolási hőmérséklet tartomán	-40...+65 °C
Tárolási relatív páratartalom tartomány	0...100 % RH (páraleszapódás nem megengedett)
Méretek	220 mm (átmérő), 250 mm (magasság)
Tömeg	kb. 900 g
Anyag	UV stabilized ASA, stainless steel
Garancia	3 év