

## CO2 távadó WiFi interfésszel, házba integrált érzékelővel

Termékkód: W5714



WiFi interfésszel rendelkező, CO2 mérésére szolgáló távadó, a távadóba integrált, azzal együtt szállított érzékelővel.

Communication with the sensor is done via a wireless WiFi network. The device allows sending measured values to the online <u>COMET Cloud</u> or <u>COMET Database</u> storage with the shortest interval of 5 minutes. The values can be displayed on integrated web pages and provided to third party systems using the Modbus TCP protocol. The measured values are displayed on the LCD display.

The device continuously evaluates the alarm limits of the measured values and in case of exceeding them, it can send an e-mail or inform by means of acoustic or optical signaling. Two alarm limits are supported for each measurement channel.

The main advantage of sensors with WiFi interface is the simplicity of deployment in places where WiFi infrastructure is already available. Just place the sensor in the desired location and connect it to the WiFi network. WiFi sensor in conjunction with <a href="COMET\_Cloud">COMET\_Cloud</a> or <a href="COMET\_Cloud">COMET\_C

Thanks to these unique features, the WiFi sensor will find applications and a wide range of application areas.

## Műszaki adatok

CO2 SENSOR	
Measuring range	0 to 5000 ppm
Accuracy	±(50ppm +3% from reading) at 25°C and 1013hPa
Resolution	1 ppm
GENERAL TECHNICAL DATA	
Operating temperature	-30 to +60 °C
Channels	internal sensor of CO2
Measuring interval	15 s
Sending interval to COMET Cloud	adjustable 5 minutes to 12 hours
Communication protocols	HTTP(S), SMTP, ModbusTCP, HTTP POST
Alarm signalization	e-mail, acoustic, LED
Power	5.0 to 5.4 VDC; consumption 300 mA (max. 500 mA); USB-C connector
Radio section	frequency: 2.4 GHz; max. transmit power: 18 dBm; standard: 802.11 b/g/n; with FCC ID: Z64-CC3220MOD
Protection class	IP30
Dimensions	81 x 93 x 32 mm
Weight	115 g
Warranty	3 years